

## 1281S4 Coax - Banana Peel® Unjacketed Bundles Mini Hi-Res Component Video



**Obsolete**  
**Call**  
**1-800-BELDEN1**

For more Information  
 please call

1-800-Belden1

**Description:**

25 AWG solid .018" tinned copper conductors, foam HDPE insulation, Duobond® foil plus a tinned copper interlocked serve shield (100% coverage), inner PVC jacket.

**Usage (Overall)****Suitable Applications:**

RGB, VGA, SVGA, XGA, SXGA, UXGA, HDTV, LCD, Plasma, Digital Signage, Component Video, Video Mult, Animation, Special effects

**Physical Characteristics (Overall)****Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
4	25	Solid	TC - Tinned Copper	.018

**Insulation****Insulation Material:**

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	.074

**Inner Shield****Inner Shield Material:**

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Aluminum Foil-Polyester Tape Lightly bonded to dielectric	100
2		Interlocked Serve	TC - Tinned Copper	95

**Inner Jacket****Inner Jacket Material:**

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.114

**Inner Jacket Color Code Chart:**

Number	Color
1	Red
2	Green
3	Blue
4	Yellow

**Outer Shield****Outer Shield Material:**

Outer Shield Material
Unshielded

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material
Unjacketed

**Overall Cabling****Overall Cabling Fillers:**

Bonded Spline

**Overall Nominal Diameter:**

0.275 in.

## 1281S4 Coax - Banana Peel® Unjacketed Bundles Mini Hi-Res Component Video

**Mechanical Characteristics (Overall)**

Operating Temperature Range:	-40°C To +75°C
UL Temperature Rating:	60°C
Non-UL Temperature Rating:	75°C
Bulk Cable Weight:	51 lbs/1000 ft.
Max. Recommended Pulling Tension:	110 lbs.
Min. Bend Radius (Each Coax):	1.100 in.
Min. Bend Radius (Overall):	3 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	02/24/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

**Flame Test**

UL Flame Test:	UL1666 Vertical Shaft
----------------	-----------------------

**Suitability**

Suitability - Indoor:	Yes - Risers
-----------------------	--------------

**Plenum/Non-Plenum**

Plenum (Y/N):	No
Plenum Number:	1282S4, 1278P

**Electrical Characteristics (Overall)****Nom. Characteristic Impedance:**

Impedance (Ohm)
75

**Nom. Inductance:**

Inductance (μH/ft)
.087

**Nom. Capacitance Conductor to Shield:**

Capacitance (pF/ft)
17.0

**Nominal Velocity of Propagation:**

VP (%)
80

**Nominal Delay:**

Delay (ns/ft)
1.24

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
--------------------------

## 1281S4 Coax - Banana Peel® Unjacketed Bundles Mini Hi-Res Component Video

34

## Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

5.4

## Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	0.52
5	1.17
50	3.7
100	4.9
200	6.7
400	9.5
750	13.4
900	15.0
1000	15.8
3000	31.2

## Max. Operating Voltage - UL:

Voltage

300 V RMS

## Max. Operating Voltage - Non-UL:

Voltage

300 V RMS

## Minimum Return Loss:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
		5	850	20

## Sweep Test

Sweep Testing:

5 - 850 MHz

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 3    Revision Date: 09-22-2008

© 2008 Belden, Inc  
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.