


## 735A16 Coax - 735A\* Series

For more Information  
please call

1-800-Belden1

**General Description:**

26 AWG solid .016" silver-plated copper conductor(s), foam HDPE insulation, Beldfoil® + tinned copper braid shield (95% coverage), PVC jacket.

**Physical Characteristics (Overall)****Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
16	26	Solid	SPC - Silver Plated Copper	.016

Total Number of Conductors: 16

**Insulation****Insulation Material:**

Insulation Material	Dia. (in.)
FHDPE - Foam High Density Polyethylene	.077

**Inner Shield****Inner Shield Material:**

Layer #	Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000
2		Braid	TC - Tinned Copper	95.000

**Inner Jacket****Inner Jacket Material:**

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	.129

**Outer Shield****Outer Shield Material:**

Outer Shield Material
Unshielded

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Outer Jacket Ripcord: Yes

**Overall Cable**

Overall Nominal Diameter: 0.636 in.

**Mechanical Characteristics (Overall)**

Operating Temperature Range: -40°C To +75°C

Bulk Cable Weight: 239 lbs/1000 ft.

Max. Recommended Pulling Tension: 400 lbs.

Min. Bend Radius (Each Coax): 0.900 in.

Min. Bend Radius (Overall): 6.500 in.

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	Telcordia Specification GR-139-Core

### Flame Test

UL Flame Test:	UL1666 Vertical Shaft
CSA Flame Test:	FT4

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

### Nom. Characteristic Impedance:

Impedance (Ohm)
75

### Nom. Inductance:

Inductance (μH/ft)
.19

### Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
17.7

### Nominal Velocity of Propagation:

VP (%)
76

### Nominal Delay:

Delay (ns/ft)
1.34

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
41

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
5.3

### Max. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.600
1.024	0.610

4.224	1.100
5.000	1.200
10.000	1.700
17.184	2.200
22.368	2.500
25.920	2.700
44.736	3.600
50.000	3.800
69.632	4.500
77.760	4.800
100.000	5.500
137.088	6.400
200.000	7.800

**Max. Operating Voltage - UL:**

<b>Voltage</b>
300 V RMS

**Other Electrical Characteristic 1:** Impedance tested in accordance with ASTM D-4566 Paragraph 43.2, Option 2 using a 75 Ohm Fixed Bridge and Termination.

**Other Electrical Characteristic 2:** RL tested in Accordance with ASTM D-4566 Paragraph 45.3, using a 75 Ohm Fixed Bridge and Termination.

**Other Electrical Characteristic 3:** 100% Sweep tested

**Minimum Return Loss:**

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
		15	95	30

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
735A16 0081000	1,000 FT	255.000 LB	GRAY		16 #26 COAX FRPVC
735A16 008500	500 FT	129.500 LB	GRAY	C	16 #26 COAX FRPVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 10-04-2012

© 2013 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.