

9201 Coax - RG-58/U Type

For more Information
please call

1-800-Belden1

**General Description:**

RG-58/U type, 20 AWG solid .033" bare copper conductor, polyethylene insulation, bare copper braid shield (80% coverage), PVC jacket.

Physical Characteristics (Overall)**Conductor****AWG:**

| # Coax | AWG | Stranding | Conductor Material | Dia. (in.) |
|--------|-----|-----------|--------------------|------------|
| 1 | 20 | Solid | BC - Bare Copper | .033 |

Total Number of Conductors: 1

Insulation**Insulation Material:**

| Insulation Material | Dia. (in.) |
|---------------------|------------|
| PE - Polyethylene | .116 |

Outer Shield**Outer Shield Material:**

| Type | Outer Shield Material | Coverage (%) |
|-------|-----------------------|--------------|
| Braid | BC - Bare Copper | 80.000 |

Outer Jacket**Outer Jacket Material:**

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Overall Cable

Overall Nominal Diameter: 0.193 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +80°C

Non-UL Temperature Rating: 75°C

Bulk Cable Weight: 23 lbs/1000 ft.

Max. Recommended Pulling Tension: 37 lbs.

Min. Bend Radius/Minor Axis: 2 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

| | |
|-----------------------------------|------|
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| RG Type: | 58/U |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)**Nom. Characteristic Impedance:**

| |
|-----------------|
| Impedance (Ohm) |
| 52 |

Nom. Inductance:

| |
|--------------------|
| Inductance (μH/ft) |
| 0.0801 |

Nom. Capacitance Conductor to Shield:

| |
|---------------------|
| Capacitance (pF/ft) |
| 28.5 |

Nominal Velocity of Propagation:

| |
|--------|
| VP (%) |
| 66 |

Nominal Delay:

| |
|---------------|
| Delay (ns/ft) |
| 1.54 |

Nom. Conductor DC Resistance:

| |
|--------------------------|
| DCR @ 20°C (Ohm/1000 ft) |
| 10.0 |

Nominal Outer Shield DC Resistance:

| |
|--------------------------|
| DCR @ 20°C (Ohm/1000 ft) |
| 5.5 |

Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100 ft.) |
|-------------|--------------------------|
| 1 | 0.3 |
| 10 | 1.1 |
| 50 | 2.5 |
| 100 | 3.8 |
| 200 | 5.6 |
| 400 | 8.4 |
| 700 | 11.7 |
| 900 | 13.7 |
| 1000 | 14.5 |

Max. Operating Voltage - Non-UL:

| |
|------------|
| Voltage |
| 1400 V RMS |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|-------|-------|---------------------------|
| 9201 010U1000 | 1,000 FT | 25.000 LB | BLACK | | #20PE BRD PVC RG58/U TYPE |
| 9201 010U500 | 500 FT | 13.000 LB | BLACK | | #20PE BRD PVC RG58/U TYPE |
| 9201 010I1000 | 1,000 FT | 25.000 LB | BLACK | C | #20PE BRD PVC RG58/U TYPE |
| 9201 010I500 | 500 FT | 13.500 LB | BLACK | | #20PE BRD PVC RG58/U TYPE |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 09-24-2012

© 2013 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.